



## Spa Maintenance

### DAILY:

- Check sanitizer level and dose as required (irrespective of whether spa is fitted with an Ozonator)
- Check pH value and dose as required

### WEEKLY

- Shock spa with suitable oxidising agent such as Non-Chlorine shock or Calcium Hypochlorite
- Add spa clarifier and an anti-foaming agent to enhance clarity and control foaming compounds if necessary
- If in an area of high calcium hardness add a dose of descaler

### MONTHLY

- Clean filter cartridge using cartridge cleaner
- Rebalance your spa water

### PERIODICALLY

- Empty and refill the spa every four to twelve weeks depending on use. As a guide, spa capacity in litres divided by daily bathers divided by 12 is a good formula example:
- 1200 litres divide by 2 daily bathers by 12 = 50 days between each draining of the spa

Measure	Desired level
Sanitizer: Chlorine	2-5mg/l (ppm)
Bromine	4-6mg/l (ppm)
pH	7.2 - 7.6
Total Alkalinity	80 -160 mg/l (ppm)
Calcium Hardness	Min 100 mg/l (ppm)

If you require any further assistance please do not hesitate to contact us, we will be more than happy to help with any questions or queries.

#### **Head Office**

3-5 Wessex Road, Ringwood, BH24 2EX

Tel: 01425 477050 Fax: 01425 477033

E-mail: [sales@ambassadorpools.co.uk](mailto:sales@ambassadorpools.co.uk)

Web: [www.ambassadorpools.co.uk](http://www.ambassadorpools.co.uk)